

Matting Additive

Special Products

A Matting Additive for use with 1-pack finishes and varnishes.



PRODUCT DESCRIPTION

A matting additive specially formulated for mixing with International one pack finishes and varnishes to produce a variety of gloss, satin or matt effect finishes.

PRODUCT INFORMATION

Colour	YMA715
Finish	Matt
Specific Gravity	1.010
Volume Solids	48%
Typical Shelf Life	2 yrs
VOC (As Supplied)	412 g/l
Unit Size	750 ml

DRYING/OVERCOATING INFORMATION

Drying

Overcoated By	Overcoating Substrate Temperature							
	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Preparation

Follow the surface preparation instructions shown on the label of the finish or varnish to which the Matting Additive is being added.

Method

Stir individual products prior to mixing. The level of gloss will decrease where the amount of Matting Additive is increased. The opacity of the chosen finish will be affected once the clear Matting Additive is added. Apply the standard finish first and finish off with the mixed (matted) material as a last coat, or apply multiple coats until full opacity is achieved. Stir well before use.

Hints

Mixing

GUIDELINES ARE AS FOLLOWS:

Toplac:

25% addition of the Matting Additive by volume to achieve up to a 30% reduction in gloss

50% addition of the Matting Additive by volume to achieve up to a 80% reduction in gloss

75% addition of the Matting Additive by volume to achieve up to a 95% reduction in gloss

For large areas, ensure full required volume of matted paint is mixed prior to commencing application.

Matt appearance may vary with colour.

Thinner YTA800 Thinners No.1

Thinning Matting Additive may be thinned by 5% prior to mixing with Topcoat or Varnish. Use Thinners No.1.

Conventional Spray (Professional spray application only) Pressure: 3-4 bar. Tip Size: 1.1-1.4 mm. For spray application of matted 1-pack varnishes or finishes, follow instructions on the datasheet for the product in question.

Other The addition of Matting Additive to a finish or varnish will not affect the drying or overcoating characteristics of the product. It will not affect the durability of the finished surface. As with all the types of reduced-gloss coatings, the resulting finish will not have the same stay-clean properties as a full-gloss coating. If all the mixed (matted) material is not used it may be used at a later date. Simply stir well before use. Testing on a non-critical area should be carried out prior to full-scale application.

Some Important Points

Formulated for exterior use.

Product temperature should be minimum 15°C/60°F and maximum 30°C/86°F.

Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F.

Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.

Compatibility/Substrates

Only suitable for use with 1-pack varnishes or finishes.

Number of Coats

Variable

Application Methods

Brush, Roller, Conventional Spray (Professional spray application only).

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Please refer to your local representative or visit www.yachtpaint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2015.

Matting Additive

Special Products

A Matting Additive for use with 1-pack finishes and varnishes.



Storage

GENERAL INFORMATION:

Exposure to air and extremes of temperature should be avoided. For the full shelf life of Matting Additive to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.

TRANSPORTATION:

Matting Additive should be kept in securely closed containers during transport and storage.

Safety

GENERAL:

Read the label safety section for Health and Safety Information, also available from our Technical Help Line.

DISPOSAL:

Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal.

Remainders of Matting Additive cannot be disposed of through the municipal waste route or dumped without permit.

Disposal of remainders must be arranged for in consultation with the authorities.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit www.yachtpaint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2015.