

Product Data Sheet

Awlgrip Repair Products



Intended Uses

Should the need arise to repair your Awlcraft SE or Awlgrip HDT coating system, from the smallest scratch through to a large scale repair, this product in conjunction with the Awlcraft SE Repair Manual and Awlgrip HDT Repair Brochure will take you through to a seamless repair.

Awlgrip Repair Products are used as part of the Awlcraft SE or Awlgrip HDT repair systems.

Specification Data

Volume Solids	Awlgrip Repair Basecoat Foundation Coat (E3001) - 10.37% (MS 13.31%) Awlgrip Repair Basecoat Blender (T0190) - 9.76% (MS 11.70%) Awlgrip Repair Topcoat Blender (T0195) - 0.025% (MS 0.03%)
Specific Gravity	Awlgrip Repair Basecoat Foundation Coat (E3001) - 0.89 Awlgrip Repair Basecoat Blender (T0190) - 0.93 Awlgrip Repair Topcoat Blender (T0195) - 0.84
Available Packs	All products are available in Quart size packs
Base	OE3001 - Awlgrip Repair Basecoat Foundation Coat OT0190 - Awlgrip Repair Basecoat Blender OT0195 - Awlgrip Repair Topcoat Blender



VOC

All VOC information contained herein is theoretical (unless otherwise stated). Actual VOC content may vary by batch and when tested via standard test methodology.

Product	As Supplied (without reducer)			
	g/L	lb/gal	g/Kg	lb/lb
OE3001	768	6.41	866	0.87
OT0190	825	6.89	883	0.88
OT0195	841	7.02	999	1



Surface Preparation

The surface preparation advice provided, and equipment suggestions, can be used as a guide. Preparation techniques and results will vary according to individual conditions, equipment choice/condition and other factors. Testing on a non-critical area should be carried out prior to full-scale preparation.

The surface preparation of the area to be repaired is described in the separate repair manuals for Awlcraft SE and Awlgrip HDT.



Mixing & Reduction

Mixing and reduction requirements will vary according to individual conditions, climate, equipment choice/condition and other factors. Mixing and application of a small sample before full-scale application is recommended.

The mixing and reduction instructions for the repair products are described in the separate repair manuals for Awlcraft SE and Awlgrip HDT.



Application

Application equipment and parameters are given as a guide. Actual equipment choices will vary according to application conditions, equipment condition and other factors. Testing on a non-critical area should be carried out prior to full-scale application. Contact your local technical service representative for further advice if necessary.

For use and application of the Awlgrip Repair Products please refer to the separate repair manuals for Awlcraft SE and Awlgrip HDT.



Recoatability & Drying Times

The data given for recoatability is not exhaustive. Actual recoatability can vary according to individual conditions, climate and surroundings. If unsure, consult your local technical service representative before proceeding.

The recoatability information and recommended drying times for the repair products are described in the separate repair manuals for Awlcraft SE and Awlgrip HDT.

Please refer to your local representative or visit <http://www.awlgrip.com> for further information.

Awlgrip, the AkzoNobel logo and other products mentioned in this publication are trademarks of AkzoNobel. ©AkzoNobel 2019

Product Data Sheet

Awlgrip Repair Products



Warning Notes

Do not use unless mixed thoroughly with the curing agent at specified ratio.

Do not use below 13°C/55°F or warmer than 40°C/104°F. Proper application and/or cure results may be more difficult to achieve when conditions are outside this range.

Avoid conditions of low temperature with high humidity as this can result in the formation of a surface by-product that must be removed by either detergent wash followed by fresh water wash, or by sanding.

Check with local authorities to determine VOC restrictions in your area.

Please ensure a risk assessment is carried out to assess the level of PPE required for the particular task undertaken when using this product.

The information in this Product Data Sheet is not intended to be exhaustive. Any person using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at their own risk and, to the extent permitted by law, we can accept no responsibility for the performance of the product or for any loss or damage arising out of such use. The information contained in this Product Data Sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit <http://www.awlgrip.com> for further information.

Awlgrip, the AkzoNobel logo and other products mentioned in this publication are trademarks of AkzoNobel. ©AkzoNobel 2019